

Print-Smart™ Vinyl Print Media



Product: **Print Smart V4 GWBOR Removable**

Technical Data

Face Material:	4 mil Calendered PVC
Finish/Color:	Gloss/White
Adhesive:	Removable Blockout
Release Liner:	130 gram Air Egress Anti Curl - Anti Wave

Typical Characteristics

Average Adhesion Values	<u>20 min</u> 21oz/sq inch	<u>24 hours</u> 46oz/sq inch
Opacity:	99%	
Outdoor Durability	4 years, vertical exposure	
Heat Resistance:	104° F to 176° F Latex Recommended	

Print-Smart V4 GWBOR is an easy to install solution for your short to medium-term removable applications. This removable air egress adhesive allows for easy installation. Print-Smart V4 GWBOR is a premium air egress vinyl for everyday sign applications. Designed for Solvent, Eco-Solvent, Latex based & UV inkjet printing systems. Double sided PE liner resists curling and waving due to humidity and high heat dryers. Printed PVC must be allowed to dry for 24-48 hours at 70°F prior to lamination to allow residual solvent to evaporate. Failure to do so may result in unsatisfactory results.

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

To place an order or get help call 1-800-276-2664
or visit our website at www.aglinc.com

Common Applications

- Trade Show Displays
- Window Graphics
- Medium Term Graphics