



Compadre™

Sheet Fed/Roll-to-Roll Laminator



- ✓ Film Tension Braking System for Process Repeatability
- ✓ Swing Up Feed Table with Webbing Diagrams
- ✓ Variable Speed Control 0 to 20 fpm
- ✓ Pneumatically controlled main nip roller - for fast response and ease of use

Fleet Graphics | Wall Coverings | Decals | Banners | Posters



Made for Small to Medium Size Shops

The Compadre is a laminator designed to satisfy the small to medium sign shop market. This laminator incorporates AGL's original nip roll design and configuration. The Compadre allows for more reliable print laminating and mounting at faster throughput speeds. It features a six inch diameter steel core covered with a high release non-crowned silicone covering. The top nip roll features preset heat assist for warming up pressure sensitive over-laminates to reduce or eliminate silvering.

Single Sided Lamination - with absolute flat output, protect your decals from fading, get great color fastness, durability, image enhancement, and increased longevity.

Mount - to any substrate effortlessly with no wrinkles, no bubbles and perfect alignment, eliminating do-over's. And do it all with a single operator.

Over-laminate and pre-mask in one pass - that's right, using AGL's Cover-Rite V2 you can cut a seven step process down to 3 steps.

Laminate banners of course! - or turn ordinary paper prints into decals to mount to any substrate, create floor graphics and more.

Tailor your inkjet output for the customer's application - Stop selling "me too" products, by using different over-laminates and processes you can separate yourself from your competition.

Other standard features include:

- Top heated roller (100 degree preset) - accelerates adhesion and reduces or eliminates silvering
- 2 Unwind supply shafts
- 1 Release liner windup
- 1 Rear product rewind
- Auto grip core chucks
- High release silicone nip rollers - for easy cleaning
- New film tension braking system for process repeat-ability
- Swing up feed table with Webbing Diagrams
- Variable Speed Control 0 to 20 fpm
- Pneumatically controlled main nip roller - for fast response and ease of use
- Rotary dial shim stops for preset gap adjustment - adjustable from -1/16 to 3/4 inch
- Working width 64 inches
- Power 120 volt 15 amp - Plug type (standard grounded)
- Tough powder coated 2 tone finish
- Foot control run switch - for hands free start and stop
- Machine dimensions - width 83"/depth 25"/height 53"



800.276.2664 • aglinc.com

Competitively Priced American Made Laminator