





- RTS Repeatable Tension System for consistent tension control
- Proprietary heated roller superior roller construction for faster heat transfers and uniform temperature across the entire width of the roll
- Variable Speed Control 0 to 20 fpm. 30 fpm with speed upgrade
- Pneumatically controlled main nip roller for fast response and ease of use

Fleet Graphics | Wall Coverings | Decals | Banners | Posters

HAGI

Made for Medium to Large Size Shops

The AGL's Encore laminator has been the workhorse for the wide format graphics industry for more than 25 years. As more and more graphic shops are experiencing laminating delays due to backups in their finishing departments. AGL announces that the Encore can process these laminating functions at a faster rate with the addition of a speed upgrade. With this option the Encore is now capable of processing speeds up to 30 FPM. This speed upgrade will allow graphic shops more productivity and finishing output for more business growth in the future.

Single Sided Lamination - Utilizing a single top heated roller design, the model SH offers you the ability to run one-sided thermal films and pressuresensitive overlaminates.

Unique Nip Roller Design - pneumatically controlled, assures and maintains a uniform pressure across the entire roll face for quality production and safe efficient operation.

Quick Latch Assembly - fast secure docking of film supply shafts.

Front & Rear Logic Control Panels - The Encore is truly a bi-directional laminator, with full access to the controls you need from both the front and rear. Including speed! Our easy to read and reach controls provide you with constant feed back and a foot operated jog switch for hands free drive operation.

Advanced Heated Roll Technology - provides a superior, reliable temperature profile across the entire roll face so you can achieve consistent quality product performance.



Other standard features include:

- Top heated roller (up to 320 degree temperature) accelerates adhesion and reduces or eliminates silvering
- 2 Unwind supply shafts
- 1 Release liner windup
- 1 Rear product rewind
- Auto grip core chucks specially designed to grip thin walled cardboard cores
- High release silicone nip rollers for easy cleaning
- Cantilevered swing out supply shafts
- Variable Speed Control 0 to 20 fpm, 30 fpm with upgrade
- Pneumatically controlled main nip roller for fast response and ease of use
- Rotary dial shim stops for preset gap adjustment adjustable from -1/16 to 3/4 inch
- Working width 62 inches
- Power 230 volt 40 amp -Plug type (standard grounded)
- Tough powder coated 2 tone finish
- Foot control run switch for hands free start and stop
- Machine dimensions width 88.5"/depth 41"/ height 50"

Proven Workhorse American Made Laminator